

Amendments to the Claims:

1. (Currently Amended) A system for pushing content to a terminal located within ~~one of a mobile network and or~~ a private network, the system comprising:

a network node located across a public network from the network including the terminal, wherein the network node is ~~capable of subscribing~~ configured to subscribe to a push service on behalf of the terminal such that the network node is also ~~capable of receiving~~ configured to receive push content in accordance with the push service, wherein the network node is thereafter ~~capable of establishing~~ configured to establish a network-initiated data session with the terminal, and wherein the network node is further ~~capable of registering~~ configured to register the terminal in response to the network-initiated data session such that the terminal is ~~capable of receiving~~ receives the push content based upon the registration.

2. (Currently Amended) A system according to Claim 1, wherein the network node is ~~capable of receiving~~ configured to receive, and thereafter ~~storing~~ store in a buffer, the push content, and wherein the network node is ~~capable of sending~~ configured to send the push content to the terminal from the buffer.

3. (Currently Amended) A system according to Claim 1, wherein the network node is ~~capable of registering~~ configured to register the terminal such that the terminal is ~~capable of subscribing~~ subscribes to the push service based upon the registration, and thereafter receiving receives the push content based upon the terminal subscribing to the push service.

4. (Currently Amended) A system according to Claim 1, wherein the network node is ~~capable of establishing~~ configured to establish a network-initiated data session with the terminal ~~by sending~~ including being configured to send a trigger to the terminal independent of the public network to thereby trigger the terminal to register with the network node.

5. (Currently Amended) A system according to Claim 1, wherein the network node

is ~~capable of receiving~~ configured to receive a registration message from the terminal across the public network to thereby identify the terminal across the public network and register the terminal, and wherein the network node is ~~capable of registering~~ configured to register the terminal such that the terminal is ~~capable of receiving~~ receives the push content based upon the identity of the terminal across the public network.

6. (Currently Amended) A system according to Claim 5, wherein the network node is ~~capable of receiving~~ configured to receive a registration message from the terminal via at least one of a network address translator (NAT) ~~and/or~~ a firewall (FW) located between the network node and the terminal, and wherein the network node is ~~capable of establishing~~ configured to establish a network-initiated data session in a manner independent of the at least one of the NAT ~~and/or~~ FW.

7. (Original) A system according to Claim 1, wherein the network node comprises a Session Initiation Protocol (SIP) proxy.

8. (Currently Amended) A method of pushing content to a terminal located within ~~one of a mobile network and/or~~ a private network, the method comprising:

subscribing to a push service from a network node located across a public network from the network including the terminal, wherein subscribing to a push service comprises subscribing to a push service on behalf of the terminal;

receiving push content at the network node in accordance with the push service;

establishing, at the network node, a network-initiated data session with the terminal;

registering the terminal with the network node in response to the network-initiated data session; and

sending the push content to the terminal based upon the registration.

9. (Original) A method according to Claim 8, wherein receiving push content at the network node further comprises storing the push content in a buffer at the network node,

and wherein sending the push content comprises sending the push content to the terminal from the buffer.

10. (Original) A method according to Claim 8 further comprising:
subscribing to the push service from the terminal based upon the registration,
wherein sending the push content comprises sending the push content to the terminal based upon subscribing to the push service from the terminal.

11. (Original) A method according to Claim 8, wherein establishing a network-initiated data session with the terminal comprises sending a trigger from the network node to the terminal independent of the public network to thereby trigger the terminal to register with the network node.

12. (Original) A method according to Claim 8, wherein registering the terminal comprises receiving a registration message at the network node from the terminal across the public network to thereby identify the terminal across the public network,
and wherein sending the push content comprises sending the push content based upon the identity of the terminal across the public network.

13. (Currently Amended) A method according to Claim 12, wherein receiving a registration message comprises receiving a registration message at the network node from the terminal via at least one of a network address translator (NAT) ~~and~~or a firewall (FW) located between the network node and the terminal,
and wherein establishing a network-initiated data session comprises establishing a network-initiated data session in a manner independent of the at least one of the NAT ~~and~~or FW.

14. (Original) A method according to Claim 8, wherein subscribing to a push service comprises subscribing to a push service from a network node comprising a Session Initiation Protocol (SIP) proxy.

15. (Currently Amended) A terminal located within ~~one of a mobile network and or a~~ private network, the terminal comprising:

a controller ~~capable of instructing configured to instruct~~ a network node to subscribe to a push service on behalf of the terminal such that the network node receives push content in accordance with the push service, the network node being located across a public network from the network including the terminal, wherein the controller is ~~capable of instructing configured to~~ instruct the network node to subscribe to the push service such that the network node also establishes a network-initiated data session with the terminal, wherein the controller is ~~capable of~~ registering configured to register the terminal with the network node in response to the network-initiated data session, and thereafter ~~receiving receive~~ the push content based upon the registration.

16. (Currently Amended) A terminal according to Claim 15, wherein the controller is ~~capable of instructing configured to instruct~~ the network node to subscribe to the push service such that the network node receives, and stores in a buffer, push content such that the controller is capable of receiving the push content from the buffer.

17. (Currently Amended) A terminal according to Claim 15, wherein the controller is ~~capable of subscribing configured to subscribe~~ to the push service based upon the registration, and wherein the controller is ~~capable of receiving configured to receive~~ the push content based upon subscribing to the push service from the terminal.

18. (Currently Amended) A terminal according to Claim 15, wherein the controller is ~~capable of receiving configured to receive~~ a trigger from the network node to the terminal independent of the public network to thereby establish a network-initiated data session and trigger the terminal to register with the network node.

19. (Currently Amended) A terminal according to Claim 15, wherein the controller is

~~capable of sending~~ configured to send a registration message to the network node across the public network to thereby identify the terminal across the public network such that the network node is ~~capable of registering~~ registers the terminal, and wherein the controller is ~~capable of receiving~~ configured to receive the push content based upon the identity of the terminal across the public network.

20. (Currently Amended) A terminal according to Claim 19, wherein the controller is ~~capable of sending~~ configured to send a registration message to the network node via at least one of a network address translator (NAT) ~~and or~~ a firewall (FW) located between the network node and the terminal, and wherein the controller is ~~capable of instructing~~ configured to instruct the network node to subscribe to the push service such that the network node establishes the network-initiated data session in a manner independent of the at least one of the NAT ~~and or~~ FW.

21. (Currently Amended) A terminal according to Claim 15, wherein the controller is ~~capable of instructing~~ configured to instruct a network node comprising a Session Initiation Protocol (SIP) proxy to subscribe to a push service on behalf of the terminal.